

INFORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

S-E-C-R-E-T

25X1

| | | | |
|----------------|--|-----------------|---------------------------------|
| COUNTRY | Poland | REPORT | |
| SUBJECT | Polish Interest in Procuring Molybdenum Abroad | DATE DISTR. | 9 September 1955 |
| DATE OF INFO. | | NO. OF PAGES | 2 |
| PLACE ACQUIRED | | REQUIREMENT NO. | RD |
| DATE ACQUIRED | | REFERENCES | This is UNEVALUATED Information |

25X1

25X1

SOURCE EVALUATIONS ARE DEFINITIVE

[] Impexmetal of Stalimored (Katowice), Poland, []
 expressed its interest in molybdenum wire and molybdenum for cores with the []
 following specifications: 25X1

25X1

25X1

Molybdenum wire for holders (Halter)

Ductility (Dehnung): 15-20%

| | |
|-------|------------------|
| 0.05 | 1,000.000 meters |
| 0.055 | 500.000 meters |
| 0.06 | 500.000 meters |
| 0.08 | 1,200.000 meters |
| 0.10 | 400.000 meters |
| 0.19 | 50.000 meters |

Ductility: 1-3%

| | |
|-------|------------------|
| 0.05 | 1,000.000 meters |
| 0.065 | 500.000 meters |
| 0.08 | 700.000 meters |
| 0.085 | 1,000.000 meters |
| 0.10 | 50.000 meters |
| 0.15 | 50.000 meters |
| 0.16 | 50.000 meters |
| 0.20 | 200.000 meters |

Ductility: 10-20%

| | |
|------|----------------|
| 0.08 | 100.000 meters |
| 0.09 | 500.000 meters |
| 0.10 | 100.000 meters |
| 0.12 | 120.000 meters |
| 0.13 | 100.000 meters |
| 0.15 | 20.000 meters |
| 0.18 | 200.000 meters |

S-E-C-R-E-T

25X1

| | | | | | | | | | | | | | |
|-------|---|------|---|------|---|-----|---|-----|---|-----|---|-----|---|
| STATE | X | ARMY | X | NAVY | X | AIR | X | FBI | X | AEC | X | ORR | X |
|-------|---|------|---|------|---|-----|---|-----|---|-----|---|-----|---|

(Note: Washington distribution indicated by "X"; Field distribution by "#")

INFORMATION REPORT INFORMATION REPORT

S-E-C-R-E-T

-2-

25X1

Molybdenum for cores

Ductility (maximum): 5%

| | |
|-------|----------------|
| 0.05 | 250.000 meters |
| 0.08 | 10.000 meters |
| 0.18 | 150.000 meters |
| 0.19 | 50.000 meters |
| 0.199 | 250.000 meters |
| 0.37 | 250.000 meters |

Samples requested of following diameter:

0.05
0.08
0.085
0.10
0.50

25X1

S-E-C-R-E-T